

SHINNOKI®

Prefinished real wood veneer

ABOUT & APPLICATIONS

Shinnoki® prefinished wood veneer laminates are made by Decospan in Belgium from real wood veneer bonded to a phenolic laminate backing sheet. Shinnoki retains the warmth and feel of real timber veneer in clear finishes and natural-coloured tints such as greys, black, smoked and lime-washed. Textures are either open-pore or lightly wire-brushed, gloss levels are around 10%. Veneer species are European Oak, American Walnut and American White Sassafras. All Shinnoki veneer laminates are FSC® Controlled for sustainability

Shinnoki is available ex-stock in twelve different designs, made by the random-matching of veneer leaves from different logs, resulting in a continuous look throughout an entire project. It is generally more economical to use than ordinary veneer because it is pre-finished, and pre-finishing also reduces fabrication times. Shinnoki is not a structural product and must be bonded to a suitable substrate such as MDF.

For more information go to <https://www.shinnoki.com/>

Briggs Veneers supplies Shinnoki as a laminate only, not glued onto substrate. For supply and prices of Shinnoki on substrate please contact us for the names of your local panel layers.

Applications

Shinnoki is suitable for use wherever wood veneers are used, i.e. interior, dry, low-wear applications, vertical and low-wear horizontal applications such as:

- Wall panelling, interior doors and furniture
- Ceiling panels, office work-stations, low-wear table- and desk-tops.
- Bathroom-vanity doors and kitchen doors if the room is properly ventilated and if the veneered panel is properly edge- banded and sealed. Note that wire-brushed laminates may be hard to clean.

It should *not* be used for:

- High and medium wear areas such as counter-fronts, floors, stair treads, desk and table tops exposed to medium or high wear, counter-tops exposed to medium/heavy wear and kitchen counter-tops
- High humidity, wet, steamy or damp conditions such as vanity tops, splash-backs or above stoves and dishwashers.
- Exterior applications such as external doors, exterior cladding and walls - even if under an awning
- Areas exposed to temperatures above 60 degrees C
- Areas around stoves and fireplaces
- Areas with prolonged exposure to direct sunlight
- Post-forming (but can be cold-bent to a curve of 230mm radii along the grain)

Consistency of appearance and change in appearance over time

Shinnoki prefinished veneer may have natural features such as pin knots, gum, figure, slanted or curved direction of grain, different leaf widths, off-centred crowns etc., and manufacturing features such as join lines, brush marks, knife-rub-marks and some variation in the stain used to colour the veneer, and a different degree of stain uptake between different sheets and within a sheet. It is made from natural wood and so may vary in appearance within and between different sheets, from samples to actual current stock and from the images on our website. Such variation is an intrinsic feature of natural wood veneer, its processing and coating/finishing and is not considered to be a defect.

Shinnoki may change colour over time, especially with exposure to natural/artificial/UV light and air/oxygen, just as the timber will. This is due to the intrinsic nature of lignin, which comprises about 30% of wood. The stains and coatings may also change colour over time with exposure to light/UV. Note also that different logs/leaves/sheets may age/change colour differently over time. Use in areas exposed to prolonged direct sunlight and/or heat will cause increased colour change and/or shrinkage, and so should be avoided. Because it is made of components that include wood and wood fibre, changes in humidity will cause Shinnoki to expand (increased humidity) or contract (decreased humidity).

We stock all the Shinnoki products shown on our website however supply of all products may be subject to stock runouts. As it is not possible to cover all associated manufacturing materials, conditions, products and methods, the end-user is responsible for carrying out the necessary tests and trials to check that the veneer, laminate, fabrication methods, associated materials and cleaning products/methods are suitable for the application.

Availability, price, sizes, cut, matching & finish

We stock all twelve of the Shinnoki products shown on our website however supply of all products may be subject to stock runouts.

	Cut / Matching	Finish/ Texture	Thick-ness	Unglued ABS edging available - please contact Briggs	Minimum cold bending radius (along the grain)	Will make Panel size 3000mm x 1200mm	Price
Shinnoki Cinnamon Triba FSC® Controlled	Crown/Qtr/Half-crown mix / Random-matched	10% gloss / Lightly wire-brushed	1mm	✓	230mm	✓	Medium / Average
Shinnoki Creamy Oak FSC® Controlled	Crown/Qtr/Half-crown mix / Random-matched	10% gloss / Lightly Wire-brushed	1mm	✓	230mm	✓	Medium / Average
Shinnoki Desert Oak FSC® Controlled	Crown/Qtr/Half-crown mix / Random-matched	10% gloss / Lightly Wire-brushed	1mm	✓	230mm	✓	Medium / Average
Shinnoki Frozen Walnut FSC® Controlled	Crown/Qtr/Half-crown mix / Random-matched	10% gloss / Open-pore	1mm	✓	230mm	✓	Medium / Average
Shinnoki Granite Walnut FSC® Controlled	Crown/Qtr/Half-crown mix / Random-matched	10% gloss / Open-pore	1mm	✓	230mm	✓	Medium / Average
Shinnoki Ivory Oak FSC® Controlled	Crown/Qtr/Half-crown mix / Random-matched	10% gloss / Lightly Wire-brushed	1mm	✓	230mm	✓	Medium / Average
Shinnoki Mineral Triba FSC® Controlled	Crown/Qtr/Half-crown mix / Random-matched	10% gloss / Lightly Wire-brushed	1mm	✓	230mm	✓	Medium / Average
Shinnoki Natural Oak FSC® Controlled	Crown/Qtr/Half-crown mix / Random-matched	10% gloss / Lightly Wire-brushed	1mm	✓	230mm	✓	Medium / Average
Shinnoki Raven Oak FSC® Controlled	Crown/Qtr/Half-crown mix / Random-matched	10% gloss / Lightly Wire-brushed	1mm	✓	230mm	✓	Medium / Average
Shinnoki Smoked Walnut FSC® Controlled	Crown/Qtr/Half-crown mix / Random-matched	10% gloss / Open-pore	1mm	✓	230mm	✓	Medium / Average
Shinnoki Stardust Walnut FSC® Controlled	Crown/Qtr/Half-crown mix / Random-matched	10% gloss / Open-pore	1mm	✓	230mm	✓	Medium / Average
Shinnoki Stone Triba FSC® Controlled	Crown/Qtr/Half-crown mix / Random-matched	10% gloss / Lightly Wire-brushed	1mm	✓	230mm	✓	Medium / Average